



TEST INSERT - 1000 SERIES

The test insert assemblies are placed between the relief valves and shut off valves (block valves).

Being able to test relief valves in place without the need for removal saves time and results in cost savings. Usually relief valves are taken out of service to be tested either in a shop or a mobile repair unit. Test inserts eliminate the need to remove the valve. This is beneficial when they are in remote locations or elevated off the ground. It takes approximately the same amount of time to remove, test and install one relief valve as to test 10 relief valves in place.

Size ¼" NPT	Part Number and Inlet Flange Ratings		
	150#	300#	600#
1"	1195-1.0-150	1195-1.0-300	1195-1.0-600
1 ½"	1195-1.5-150	1195-1.5-300	1195-1.5-600
2"	1195-2.0-150	1195-2.0-300	1195-2.0-600
2 ½"	1195-2.5-150	1195-2.5-300	1195-2.5-600
3"	1195-3.0-150	1195-3.0-300	1195-3.0-600
4"	1195-4.0-150	1195-4.0-300	1195-4.0-600
6"	1195-6.0-150	1195-6.0-300	1195-6.0-600
8"	1195-8.0-150	1195-8.0-300	1195-8.0-600



Size ½" NPT	Part Number and Inlet Flange Ratings		
	150#	300#	600#
1"	1196-1.0-150	1196-1.0-300	1196-1.0-600
1 ½"	1196-1.5-150	1196-1.5-300	1196-1.5-600
2"	1196-2.0-150	1196-2.0-300	1196-2.0-600
2 ½"	1196-2.5-150	1196-2.5-300	1196-2.5-600
3"	1196-3.0-150	1196-3.0-300	1196-3.0-600
4"	1196-4.0-150	1196-4.0-300	1196-4.0-600
6"	1196-6.0-150	1196-6.0-300	1196-6.0-600
8"	1196-8.0-150	1196-8.0-300	1196-8.0-600

Typical dimensions are listed. Data contained herein can be altered to accommodate design changes and changes to increase performance.

Information on this page is the sole property of L6 Inc. d/b/a Total Valve Systems.