




CHECK VALVE – 3230

3230 Series Back Pressure Check Valves are designed for use in liquid or vapor service for bulk storage tanks where flow is desired in only one direction. The 3230 Series has female NPT connections on the inlet side and male NPT connections on the outlet side. These valves can also be used as a vacuum breaker or low-pressure relief device.



	A Inlet Connection	B Outlet Connection	C Orifice Dia.	D Length	Outside Dia.
3230-G	1 ½" FNPT	1 ½" MNPT	0.80	3 3/5"	2 3/8" Hex
3230-I	2" FNPT	2" MNPT	1.10	4 ¾"	2 7/8" Hex
3230-K	3" FNPT	3" MNPT	1.65	6 7/8"	4" Hex
3230-L	4" FNPT	4" MNPT	2.20	8 ½"	5 ½" Rnd




Different size end connections are available.


Typical dimensions are listed. Data contained herein can be altered to accommodate design changes and changes to increase performance. Information on this page is the sole property of L6 Inc. d/b/a Total Valve Systems.

CHECK VALVE – 3240

3240 Series Back Pressure Check Valves are designed for use in liquid or vapor service for bulk storage tanks where flow is desired in only one direction. 3240 Series has male NPT connections on the inlet side and female NPT connections on the outlet side. These valves can also be used as a vacuum breaker or low-pressure relief device.



	A Inlet Connection	B Outlet Connection	C Orifice Dia.	D Length	Outside Dia.
3240-G	1 ½" MNPT	1 ½" FNPT	0.80	3 3/5"	2 3/8" Hex
3240-I	2" MNPT	2" FNPT	1.10	4 ¾"	2 7/8" Hex
3240-K	3" MNPT	3" FNPT	1.65	6 7/8"	4" Hex
3240-L	4" MNPT	4" FNPT	2.20	8 ½"	5 ½" Rnd



Different size end connections are available